

NAME

glarendx - calculate glare index

SYNOPSIS

glarendx -t type [-h] [glarefile]

DESCRIPTION

Glarendx computes the selected glare index *type* from the given *glarefile* produced by *findglare(1)*. *Glarendx* computes one value for each (indirect illuminance) angle in the input file. If no *glarefile* is given, *glarendx* reads from the standard input. The *-h* option can be used to remove the information header from the output.

Glarendx understands the following arguments for *type*:

guth_vcp	Guth Visual Comfort Probability
cie_cgi	CIE Glare Index (Einhorn)
ugrUnified	Unified Glare Rating
brs_gi	BRS Glare Index
dgiDaylight	Daylight Glare Index
guth_dgr	Guth Disability Glare Rating
vert_dir	Direct Vertical Illuminance
vert_ill	Total Vertical Illuminance
vert_ind	Indirect Vertical Illuminance

Alternatively, a symbolic or hard link to the program with any of the above names may be used in place of the *type* argument.

AUTHORS

Greg Ward, Raphael Compagnon

ACKNOWLEDGEMENT

Work on this program was initiated and sponsored by the LESO group at EPFL in Switzerland.

SEE ALSO

findglare(1), glare(1), igrph(1), rpict(1), xglaresrc(1), ximage(1)